
# Design of a Component-Based Augmented Reality Framework

Martin Bauer, Bernd Bruegge, Gudrun Klinker, Asa MacWilliams, Thomas Reicher, Stefan Riss, Christian Sandor, Martin Wagner *Technische Universität München* 

Institut für Informatik





# Summary

- We think the time has come for augmented reality frameworks
- This will allow software components to be reused between different AR applications
- We have built and tested a first version of such a framework, called DWARF

## Outline


- Advantages of an AR framework
- Necessary elements of an AR framework
- DWARF architecture and components
- Demonstration system

## Advantages– Project manager

- Components can be reused in different applications
- Components are "black boxes" for other components
- Distribute development in time and space
- Rapid prototyping of AR applications becomes feasible


#### Advantages- User

- Software is integrated with hardware in wearable or stationary *modules*
- System is reconfigured by re-plugging modules




## Advantages- Application developer

- System consists of layered services
- Application is modeled by configuring services



### Advantages- Module developer

- Modules are hardware with software services
- Services provide basic functionality, e.g. tracking
- Services have needs and abilities



## Elements of an AR framework


- Services providing general functionality

   General enough to reuse, yet also efficient
- Architecture to fit the services together
  - Generalization of many different AR systems
- Middleware to let services communicate
  - Must allow fast yet flexible communication

### **DWARF–** Main services

- Distributed Wearable Augmented Reality Framework as test of framework concepts
- First DWARF services cover the basic functionalities for AR applications
  - World model, optical tracker, GPS/compass tracker, tracking manager, user interface engine,VRML viewer, HTML viewer, voice recognition, taskflow engine, context router
- Implementation of services uses wellestablished and third-party technology


#### **DWARF–** Generic architecture



ISAR 2001, Oct. 29 Asa MacWilliams Slide 10 of 16


#### DWARF-Middleware


- To find each other spontaneously and communicate with one another, the DWARF services use CORBAbased Middleware
- This is distributed as local Service Managers on each hardware node to provide fault tolerance



#### Demo system– Navigation scenario

- Indoor and outdoor campus navigation system
- Wireless access to external services
- 2D maps, 3D maps and AR overlays





## Demo system – Using the framework

- Nearly entire functionality is handled by the **DWARF** services
  - Navigation sequence, campus geography, multimodal I/O, printer location, outdoor tracking, indoor tracking, 3D rendering
- Application design is greatly simplified
  - Model campus and navigation in markup languages
  - Bootstrapping, glue logic
- Application implemented in three weeks' time

#### Demo system– Hardware

- Backpack system for demonstration of software
- Two laptops running Windows NT and 98
- Glasstron see-though HMD, FireWire Camera for Optical Tracking, commercial GPS receiver, Bluetooth / WaveLAN wireless communication
- Battery-powered, > 2 hours of operation



### Conclusion

- The time has come for AR frameworks
  - Technology is becoming mature
  - Number of AR research groups is increasing
- We have investigated the feasibility of AR frameworks
  - Componentization is workable
  - Performance does not suffer from distribution
  - Rapid application development becomes possible
- We would like to encourage a discussion on framework components and technology.

# Thank you

• Any questions?