

# Image Deconvolution Parameter Estimation in Linear Inverse Problems

Thomas Kasper

Chair for Computer Aided Medical Procedures & Augmented Reality  
Department of Computer Science, TUM



Fraunhofer Institut  
Integrierte Schaltungen

November 10, 2006

## Contents

### Why not ML?

A naive approach...

...with disastrous result

### Robust Parameter Estimation

Overview

Hardware Adaptation

Results

# Inverse Problems

## A class of its own?

- ▶ Estimating ‘cause’ giving rise to observed ‘effect’
- ▶ Physical concepts not always meaningful
- ▶ Not a rigorous definition

# Linear Inverse Problems

## Special case deconvolution

Let  $f$  and  $g$  denote pristine and blurred image respectively

$$g(s) = \int_D K(s - t) f(t) dt + \nu(s)$$

where  $K$  an appropriate blur kernel and  $\nu$  random noise

## Discrete Model

$$g = Af + \nu$$

Parameter estimation problem: given  $g$  and  $A$ , find  $f$ !

# Maximum Likelihood Estimator

## Gaussian Noise

Suppose noise  $\nu \sim \mathcal{N}(0, \Phi)$  is zero-mean Gaussian. Seek  $f$  s. t.

$$\log p(g|f) = c - \frac{(g - Af)^T \Phi^{-1} (g - Af)}{2} = \max!$$

## Prewhitening Filter

A simple transformation...

$$g' = \Phi^{-1/2} g$$

$$A' = \Phi^{-1/2} A$$

# Maximum Likelihood Estimator

ML  $\equiv$  LS

...yields an equivalent Least Squares Problem

$$\arg \max \log p(g|f) = \arg \min \|g' - A'f\|_2$$

Solution

$$\hat{f}_{ML} = A'^+ g'$$

is the ML and BLU (Best Linear Unbiased) Estimator!


# If it is that simple...

Then why have someone study this class of problems during 6 months?

- ▶ waste of manpower ( $\approx 1000\text{h}!$ )
- ▶ waste of resources (yet another blocked MATLAB-License...)
- ▶ waste of money (at least I was cheap...)



# What it's really worth...

Blurred with Gaussian kernel



# What it's really worth...

Blurred with Gaussian kernel



ML Estimate and BLUE

(?)

Not quite so simple, then...

Ok, what went wrong here?

- ▶ Inverse computed by FFT
- ▶ Orthogonal Transform
- ▶ Numerically as well-behaved as can be ( $\kappa = 1$ )
- ▶ Rounding error  $\epsilon \approx 2 \times 10^{-16}$

Problem: Amplification of Noise

For most cases of practical interest  $\text{Var}(\hat{f}_{ML}) \approx \infty$

# Inverse Problems need Regularization!

# Robust Parameter Estimation

## What we *cannot* do

- ▶ Noisy environment provokes loss of information
- ▶ Complete restoration not a realistic expectation

## In what sense 'robust', then?

- ▶ Ensure that deterioration is gradual rather than abrupt
- ▶ Make solution depend continuously on the data

Tarantola, Inverse Problem Theory and Methods for Model Parameter Estimation, 2005

# 'Classical' Techniques

## Mean (Integrated) Square Error

Construct estimator for deterministic parameter  $f$  with minimal

$$MISE(\hat{f}) = E \left\{ \|\hat{f}(g) - f\|_2^2 \right\} = \|\text{Bias}(\hat{f})\|_2^2 + \text{trace}(\text{Var}(\hat{f}))$$

Idea: trade variance for bias

Accept systematic error, obtain stability in turn

$$\underbrace{\begin{pmatrix} 0 \\ \infty \end{pmatrix}}_{\hat{f}_{ML} = A^+} \quad \longleftarrow \quad \underbrace{\begin{pmatrix} \text{Bias}(\hat{f}) \\ \text{Var}(\hat{f}) \end{pmatrix}}_{\hat{f}_{mmse} = ?} \quad \longrightarrow \quad \underbrace{\begin{pmatrix} f \\ 0 \end{pmatrix}}_{\hat{f}_{triv} \equiv 0}$$

# Open questions and where to look for answers...

## How to parameterize Trade-Off-Curve?

→ Filter Functions

- ▶ Ridge Regression (Tikhonov)
- ▶ Truncated SVD ('Spectral-Cut-Off')

## Where to look for a minimizer?

→ Parameter Rules

- ▶ Generalized Cross Validation (GCV)
- ▶ L-Curve

Wahba, Practical Approximate Solutions to Linear Operator Equations, 1977

Hansen, The L-Curve and its Use in the Numerical Treatment of Inverse Problems, 2001

# Bayesian Approach

## Recast the Problem

Model the parameter  $f$  as a random variable with (non-flat) pdf


## Optimality of the Conditional Mean

Let  $\hat{f}_{mmse}(g) := E\{f|g\}$ . Then for any estimator  $\hat{f}$

$$MISE(\hat{f}) \geq MISE(\hat{f}_{mmse})$$

# Special Case: Multivariate Gaussian


Pdf of a bivariate Gaussian  
 $X = (x_1, x_2)$



What is  $f_{x_1|x_2}(x_1 | x_2 = -0.5)$  ?

# Special Case: Multivariate Gaussian

Conditional density  
 $f_{x_1|x_2}(x_1 | x_2 = 0.5)$



is (unnormalized) univariate Gaussian!

# Special Case: Multivariate Gaussian

## Conditional Mean of a multivariate Gaussian

Let  $f, g$  be two random variables with jointly Gaussian pdf

$$\begin{pmatrix} f \\ g \end{pmatrix} \sim \mathcal{N} \left( \begin{pmatrix} \mu_f \\ \mu_g \end{pmatrix}, \begin{pmatrix} \text{Var}[f] & \text{Cov}(f, g) \\ \text{Cov}(g, f) & \text{Var}[g] \end{pmatrix} \right)$$

Then

$$f|g \sim \mathcal{N}(\mu_{f|g}, \Phi_{f|g})$$

is also Gaussian with mean

$$\begin{aligned} \mu_{f|g} &= \underbrace{\mu_f + \text{Cov}(f, g) \text{Var}[g]^{-1} (g - \mu_g)}_{= \hat{f}_{mmse}(g)} \\ &= \hat{f}_{mmse}(g) \end{aligned}$$

# Wiener Filter: Gaussian Case

## Optimal Linear Estimator

Seek affine linear mapping  $g \mapsto \hat{f}_W(g)$  such that

$$MISE(\hat{f}_W) = \min!$$

For the special case of Gaussian RVs

we already know that  $\hat{f}_{mmse}$  is affine linear in  $g$ , hence

$$\hat{f}_W = \hat{f}_{mmse} : g \mapsto \mu_f + \text{Cov}(f, g) \text{Var}[g]^{-1} (g - \mu_g)$$

# Wiener Filter: General Case

Even in the general case


where  $\hat{f}_{mmse}$  is not affine linear, one can show that

$$\hat{f}_W : g \mapsto \mu_f + \text{Cov}(f, g) \text{Var}[g]^{-1} (g - \mu_g)$$

is still the best linear approximation, even though

$$\hat{f}_W(g) \neq E\{f|g\} = \hat{f}_{mmse}(g)$$



Let's test it...



Blurred with Gaussian kernel

Pretty good, isn't it?



Blurred with Gaussian kernel



Wiener Estimate

Even with a decent amount of noise...

Blurred plus white noise  
 $\sigma^2 = 25$  (SNR = 32.4737 dB)





Wiener Estimate

(!)

# Compare with the original

Pristine image



Wiener Estimate

(!)

# Implemented Algorithms (C++)

## Wiener Filter

- ▶ Direct approach

## Richardson-Lucy

- ▶ EM-based, iterative
- ▶ Poissonian noise model

## Blind Deconvolution

- ▶ EM-based, iterative
- ▶ Gaussian noise model
- ▶ Gaussian image model
- ▶ Unknown blur kernel

## Neelamani

- ▶ Hybrid approach
- ▶ Alternate filtering in Fourier/Wavelet-domain

Katsaggelos, Digital Image Restoration, 1991

Neelamani *et al.*, ForWaRD: Fourier-Wavelet Regularized Deconvolution for Ill-Conditioned Systems, 2004

# Error Metric


## Evaluation Criterion

Assessment by square error, averaged over the spatial coordinates

$$ASE(\hat{f}) = \left\| \hat{f} - f \right\|_2^2 / \dim(f)$$

where  $\hat{f}$  is the estimate of the pristine image  $f$

# Evaluation: Results



Test-image	WF	RL	BEM	NE
Blurred	22.2589	24.3831	148.6752	21.9385
Blurred& Noisy	47.903	68.1796	207.6493	56.551

# Hardware Adaptation

## Model-Problem

- ▶ Solution not well-determined by the data
- ▶ Incorporation of a-priori knowledge crucial for success

## Hardware

Component	Manufacturer/Specification
Microscope	Zeiss Axio Imager M1, dry
Lens	Zeiss Achromplan 63x, 0,95 numerical aperture
CCD-camera	JAI Pulnix TMC-1402 CL (1392x1040 and 800x600)

# CCD-Camera Noise: Covariances

Given  $k = 100$  iid darkframe images, estimate covariances!

Sample covariance matrix (=sum of rank-one updates)

$$\bar{C} = \frac{1}{k-1} \sum_{i=1}^k (\nu_i - \bar{\nu})(\nu_i - \bar{\nu})^T$$

## Problem

For high-dimensional  $\nu$  cov. are poorly determined by 100 samples!

$$\text{rank}(\bar{C}) \leq k \ll \dim(\nu) = 800 \times 600$$

# CCD-Camera Noise: Covariances

Idea: Use additional 'information'


Wide-Sense-Stationarity (WSS) assumption

- ▶ Constant mean
- ▶ Correlation is function of 2D-distance
- ▶  $\text{Var}[\nu]$  is Block-Toeplitz with Toeplitz Blocks (BTTB)

## Agenda


Construct unbiased estimator for WSS-random-processes!

# Test on synthetically created data




# Application to darkframe images

## Auto-Covariance of CCD-camera noise





# Test with ‘authentic’ data

Recorded image




# Test with ‘authentic’ data

Recorded image




Richardson-Lucy estimate

# Application to endoscopic imaging (recorded)



# Application to endoscopic imaging (deconvolved)



# Conclusion

## Linear Inverse Problems

- ▶ Well-investigated class of problems
- ▶ Particularly simple, because linear
- ▶ Practical relevance for a wide range of applications

Suggested further reading :-)

<http://home.cs.tum.edu/~kasper/da/thesis.pdf>